



## 72W NARROW ANGLE FLOODLIGHT

LED floodlight suitable for situations where narrow angle target lighting is required.

Unlike most COB or SMD floodlights, which typically have a beam angle between 90° and 120°, the design of this fitting with an array of individual LEDs (each with their own lens) enables it to produce a beam as narrow as 30°.

This fitting contains an integral Meanwell LED driver which can be supplied with a 1-10V dimming option.

Suitable for interior or exterior use.

**product no.** FL-NA-72W

**power** 72W (48 X 1.5W LEDs)

**colour** black  
also available to order in grey or silver

**tempered glass** clear  
also available to order with fogged glass

**LED type** bridgelux 45mil

**input voltage** 85 - 265V AC 50/60 Hz

**LED power** 61 - 66 W

**system power** 68 - 73 W

**power factor** >0.95

**luminous flux** 5400 - 5700 lm

**system efficiency** 75 - 85 lm/W

**colour temperature** 3000k / 4500k / 6000k

**CRI**  $R_a >70$

**beam angle** 30°

**driver output voltage** 36 - 42 V DC

**driver output current** 1600mA CC

**IP rating** IP66

**working temperature** -20°C - +50°C

**working humidity** 10% - 90% RH

**power cable** 1.5m HO5RN-F

**net weight** 4.8kg