







10W FIRE-RATED FIXED DOWNLIGHT

Fire rated fixed downlight (tested to BS476 - 90mins) with dimmable driver.

Designed to be a warm white LED equivalent for a traditional 12V 50W halogen fitting with an MR16 M(2)58 38° lamp and a dimmable electronic transformer in situations requiring fire rated downlights.

This fitting is sealed to IP65 and supplied with a silicone gasket, making it suitable for use in bathroom and shower enclosures. For special applications this fitting can be supplied in a range of colour temperatures and beam angles.

product no. FRDL-10W-40D

power 10W

7W and 13W versions available to order

beam angle 40°

other beam angles available to order

material steel and aluminium alloy

installation recessed

colour matt white

IP rating IP65

dimensions d85mm x h65mm

cutout diameter 75mm

recess depth 60mm

LED module COB sharp

colour temperature 3000K (warm white)

natural white and cool white also available to order

CRI R_a >85

lumen output 760-800 lm

LED life span 50,000 hrs

LED DRIVER

triac dimmable with leading edge or trailing edge

dimensions 98mm x 39mm x 22mm

primary 220-240V AC 50/60Hz 0.08A

secondary 260mA 29-46V DC

power factor $\lambda = 0.95$

ta -20°C - +50°C

tc 80°C